



14 cm

12 dB



ICE Model



Revolutionary 15 air-guiding Fan Blades for unprecedented airflow performance with ultra-low noise level.

Exclusive FLUXUS PRO II bearing based in Fluid Dynamic Bearing Technology for more than 200.000 hrs lifespan and ultra-silent operation.

- Special Voltage reduction cable included for Ultra-performance or Ultra-quiet operation.
- Professional Anti-vibration screws, 3-4pin adaptor and black sleeved cables included.
- Ultra-silent: 12dB-20dB and Ultra-Airflow: 50-90 CFM
- Four White leds for COOL lighting effect.

Standard Connection

| | |
|--------------------|----------------------------|
| Rated Voltage: | 12V |
| Starting Voltage: | ≤ 6.0V |
| Power Consumption: | 3.6W |
| Rated Current: | 0.30A |
| Speed: | 1200 RPM±10% |
| Air Flow: | 90 CFM |
| Air Pressure: | 0.931 mm -H ₂ O |
| Noise: | 20dBA |
| MTBF: | 200.000 hours |

Connect with Voltage reduction cable

| | |
|--------------------|----------------------------|
| Rated Voltage: | (To FAN) 7V |
| Starting Voltage: | ≤ 6.0V |
| Power Consumption: | 1.56W |
| Rated Current: | 0.13A |
| Speed: | 700 RPM±10% |
| Air Flow: | 50 CFM |
| Air Pressure: | 0.414 mm -H ₂ O |
| Noise: | 12dBA |
| MTBF: | 200.000 hours |

DESIGNED IN EUROPE